











gear pitch. This reduction in size will significantly reduce the inertia of the assembly.

Future iterations of this design will incorporate a torque sensor on the output shaft to allow force control to be implemented using an admittance approach.

#### REFERENCES

- [1] A. Krieger, R. C. Susil, C. Menard *et al.*, "Design of a novel MRI compatible manipulator for image guided prostate interventions," *Biomedical Engineering, IEEE Transactions on*, vol. 52, no. 2, pp. 306-313, 2005.
- [2] P. W. Mewes, J. Tokuda, S. P. DiMaio *et al.*, "Integrated system for robot-assisted in prostate biopsy in closed MRI scanner." pp. 2959-2962.
- [3] G. S. Fischer, I. Iordachita, C. Csoma *et al.*, "MRI-Compatible Pneumatic Robot for Transperineal Prostate Needle Placement," *Mechatronics, IEEE/ASME Transactions on*, vol. 13, no. 3, pp. 295-305, 2008.
- [4] N. V. Tsekos, J. Shudy, E. Yacoub *et al.*, "Development of a robotic device for MRI-guided interventions in the breast." pp. 201-208.
- [5] X. Zhai, R. Harter, C. Moran *et al.*, "Image-guided interventional device for 3D access and localization of breast lesions."
- [6] B. T. Larson, N. V. Tsekos, and A. G. Erdman, "A robotic device for minimally invasive breast interventions with real-time MRI guidance." pp. 190-197.
- [7] R. Kokes, K. Lister, R. Gullapalli *et al.*, "Towards a needle driver robot for radiofrequency ablation of tumors under continuous MRI." pp. 2509-2514.
- [8] Y. Ningbo, C. Hollnagel, A. Blickenstorfer *et al.*, "Comparison of MRI-Compatible Mechatronic Systems With Hydrodynamic and Pneumatic Actuation," *Mechatronics, IEEE/ASME Transactions on*, vol. 13, no. 3, pp. 268-277, 2008.
- [9] M. Flueckiger, M. Bullo, D. Chapuis *et al.*, "fMRI compatible haptic interface actuated with traveling wave ultrasonic motor." pp. 2075-2082 Vol. 3.
- [10] Y. Ningbo, W. Murr, A. Blickenstorfer *et al.*, "An fMRI compatible haptic interface with pneumatic actuation." pp. 714-720.
- [11] D. Chapuis, R. Gassert, G. Ganesh *et al.*, "Investigation of a Cable Transmission for the Actuation of MR Compatible Haptic Interfaces." pp. 426-431.
- [12] N. V. Tsekos, A. Khanicheh, E. Christoforou *et al.*, "Magnetic Resonance Compatible Robotic and Mechatronics Systems for Image-Guided Interventions and Rehabilitation: A Review Study," *Annual Review of Biomedical Engineering*, vol. 9, no. 1, pp. 351-387, 2007.
- [13] R. Gassert, R. Moser, E. Burdet *et al.*, "MRI/fMRI-compatible robotic system with force feedback for interaction with human motion," *Mechatronics, IEEE/ASME Transactions on*, vol. 11, no. 2, pp. 216-224, 2006.
- [14] N. Vanello, V. Hartwig, M. Tesconi *et al.*, "Sensing Glove for Brain Studies: Design and Assessment of Its Compatibility for fMRI With a Robust Test," *Mechatronics, IEEE/ASME Transactions on*, vol. 13, no. 3, pp. 345-354, 2008.
- [15] K. Uffmann, and M. E. Ladd, "Actuation Systems for MR Elastography," *Engineering in Medicine and Biology Magazine, IEEE*, vol. 27, no. 3, pp. 28-34, 2008.
- [16] G. Ganesh, R. Gassert, E. Burdet *et al.*, "Dynamics and control of an MRI compatible master-slave system with hydrostatic transmission." pp. 1288-1294 Vol.2.
- [17] M. Rajendra, A. Yamamoto, T. Oda *et al.*, "Motion Generation in MR Environment Using Electrostatic Film Motor for Motion-Triggered Cine-MRI," *Mechatronics, IEEE/ASME Transactions on*, vol. 13, no. 3, pp. 278-285, 2008.
- [18] B. Vigar, D. Petrisor, A. Patriciu *et al.*, "MR compatible actuation for medical instrumentation." pp. 49-52.
- [19] F. Carpi, A. Khanicheh, C. Mavroidis *et al.*, "MRI Compatibility of Silicone-Made Contractile Dielectric Elastomer Actuators," *Mechatronics, IEEE/ASME Transactions on*, vol. 13, no. 3, pp. 370-374, 2008.
- [20] I. Bricault, N. Zemiti, E. Jouniaux *et al.*, "Light Puncture Robot for CT and MRI Interventions," *Engineering in Medicine and Biology Magazine, IEEE*, vol. 27, no. 3, pp. 42-50, 2008.
- [21] R. Moser, R. Gassert, E. Burdet *et al.*, "An MR compatible robot technology." pp. 670-675 vol.1.
- [22] D. Chapuis, X. Michel, R. Gassert *et al.*, "A Haptic Knob with a Hybrid Ultrasonic Motor and Powder Clutch Actuator." pp. 200-205.
- [23] R. H. Cannon, and E. Schmitz, "Initial experiments on the end-point control of a flexible one-link robot," *International Journal of Robotics Research*, vol. 3, no. 3, pp. 62-75, 1984.